



PAD Plotter



▲ PJET-2-165/PJET-2-180/PJET-2-205

PAD Plotter comes with 4 different models — PJET-2-120, PJET-2-165, PJET-2-180 and PJET-2-205. PAD Plotter has simple but durable machine design; it comes with latest PAD developed plotting center; and it has built-in memory chip to store plotting parameters, so that you will never have to afraid of loss of the settings.

Highlights

- ▶ HP45 Print heads control card
- ▶ Communication port: USB
- ▶ Plotting control center fully developed by PAD
- ▶ Built-in memory chip stores plotting parameters
- ▶ Simple but durable machine design



▲ PJET-2-120

Technical Specifications

Product model#	PJET-2-120	PJET-2-165	PJET-2-180	PJET-2-205
Max. width of plotting paper	160 cm	173 cm	198 cm	235 cm
Max. plotting width	120 cm	165 cm	182 cm	205 cm
Actual plotter dimension (LxDxH)	193x50x104cm	246x70x110cm	275x70x110cm	300x70x110cm
Scanning speed	135 sqm / hr			
Protocol languages	HPGL ; HPGL2			
Roll feeding position	Front floor loading			
Paper take-up roll position	Ergonomic waist-level, off loading from front			
Inkjet cartridges	HP 51645A cartridge x 2			
Resolution	300 ~ 600 dpi			
Supported image formats	jpg, png, bmp, ...			
Power supply	220 VAC ; 50 Hz (or 110 VAC option to choose)			
Paper type	Recycled or bond paper (supports up to 23 cm diameter)			
PC interface	USB			
Operation panel	Ease-to-use and durable number keypad			
Working environment	<ul style="list-style-type: none"> ▶ Temperature : 0 ~ 35°C ▶ Humidity : 20% ~ 80% 			